

Wamsler puuliedet ja -takat

- tekninen informaatio:



Malli		K 144 S/C	K 155 S/C	K 140 S/C	K 150 S/C	K 118 CL K 118	Nostalgieherd K 128 CL, K 128	Nostalgieherd K 138 CL, K 138	K 138 JH	K 170 K	K 175
Hyväksyntä		CE, 15aB-VG, VKF	CE, 15aB-VG, VKF	CE, 15aB-VG, VKF	CE, 15aB-VG, VKF	CE, 15aB-VG, VKF	CE, 15aB-VG, VKF	CE, 15aB-VG, VKF	CE, 15aB-VG, VKF	CE, 15aB-V	CE, 15aB-VG, VK
Nimellisteho	kW	5	5	5	7	6	7	7	7	10	6
Tehoalue (säädettävissä)	kW	2,5–5,6	2,5–5,6	2,1–5,7	3,1–7,1	3,2–6,4	3,3–7,7	3,3–7,7	3,3–7,7	3,4–10,4	3,2–6,4
Hormiliitos	mmØ	120	120	120	130	120	120	120	120	150	120
	L	–	–	–	–	–	–	10	10	17	–
Päästöt	g/s	6,5	6,5	6,2	8,4	8	8	8	8	12,8	8
Savukaasujen ulostulolämpötila	°C	280	280	310	310	215	220	220	220	290	215
Mitat											
Leveys/syvyys		400/600/850+50	500/600/850+50	400/600/850+50	500/600/850+50	600/600/850+50	715/600/850+50	905/600/850+50	1070/680/850	1110/600/850	750/600/85
Korkeus (ilman kannta)									lev. ja syv. sis. kaitteen		
Liesitaso lev/syv	mm	343/543	442/543	343/543	442/543	543/490	658/490	848/490	849/490	835/510	695/490
	mm	190/210	190/210	150/320	180/370	150/370	180/370	180/370	180/370	200/410	150/370
Tulipesän korkeus min/max	mm	205/375	205/375	215/310	215/310	200/310	200/310	200/310	200/310	280/470	200/310
Tulipesän luukku lev/kork	mm	193/123	193/123	168/143	168/143	138/176	160/195	160/195	160/195	180/200	140/175
Uuni lev/kork/syv	mm	–	–	–	–	300/270/410	360/270/450	360/270/450	360/270/450	460/360/420	300/270/41
Suojaetäisyys palavaan materiaaliin sivussa, oik/vas takana	mm	200/200	200/200	200/200	200/200	200/250	200/300	200/300	200/300	200/200	200/250
	mm	200	200	200	200	200	200	200	200	200	200
Lisävarusteet											
Hormiliitin päälle-asennukseen		+	+	+							
Kaide		–	+	–	+	•/+	•/+	•/+	•	+	•
Eristetty päällikansi		•/+/-	•/+/-	+/-	+/-	+	+	+	–	–	–
Uuunipelti ja -ritilä		–	–	–	–	•	•	•	•	•	•
Hiilihanko		•	•	•	•	•	•	•	•	•	•
Kannen kahva		•	•	•	•	•	•	•	•	•	•
Nakirapsutin		–	–	•	•	•	•	•	•	•	•
Vesihaude lev/kork/syv	mm	–	–	–	–	–	–	120/320/265	120/320/265	170/330/300	–
Eristekappaleet keittiökaluaseennukseen	lev mm	+55 +110	+55 +110	+55 +110	+55 +110	+55 +110	+55 +110	+55 +110	–	+55 +110	+55 +110
Brutto-/nettopaino		113/108	122/115	110/101	125/111	130/120	160/150	185/170	172/154	255/225	141/129

Hormiliitoksen sijainti Wamsler-liesissä



Malli	K 144 S/C	K 155 S/C	K 140 S/C	K 150 S/C	K 118 CL K 118	K 128 CL K 128	K 138 CL K 138	K 138 JH	K 170	K 175
-------	-----------	-----------	-----------	-----------	-------------------	-------------------	-------------------	----------	-------	-------

Hormiliitos

a ¹ /a ² = lattias- hormin keskelle taakse/sivulle	mm	690(+50)	690(+50)	670(+50)	670(+50)	678(+50)	694(+50) ⁵⁾ 678(+50)	678(+50)	677 ainoastaan taakse	690	678(+50)
b = sivulle hormin keskelle takana	mm	200	250	200	250	104	124	104	141 kaiteesta	149	104
c = seinästä hormin keskelle sivulla	mm	163	163	139	170	177	177	177	-	165	177
d = sivulle hormin keskelle päällä	mm	200 ⁶⁾	250 ⁶⁾	200 ⁶⁾	250 ⁶⁾	134 ⁶⁾	134 ⁶⁾	128 ⁶⁾	164 kaiteesta	130	111
e = seinästä hormin keskelle päällä	mm	151 ⁶⁾	151 ⁶⁾	135 ⁶⁾	170 ⁶⁾	188 ⁶⁾	188 ⁶⁾	161 ⁶⁾	171	138	172

⁶⁾ ei saatavissa keraamisella liesitasolla varustettuun C - malliin

Liedet



Uunilliset liedet

